

▼ Lubricant Quality

Lubricant			Classification	
Engine oil			Refer to the recommended SAE viscosity numbers on page 8-18.	
Manual transaxle oil	2.3-liter engine	Any temperature	API Service	GL-4 or GL-5
			SAE	75W-90
	Above 10°C (50°F)	API Service	GL-4 or GL-5	
		SAE	80W-90	
	3.0-liter engine	API Service	GL-4 or GL-5	
		SAE	75W-90	
Automatic transaxle fluid		2.3-liter engine	ATF M-V	
		3.0-liter engine	JWS3309	
Power steering fluid			ATF M-V, or equivalent (e.g. Dexron® III)	
Brake fluid			SAE J1703, or FMVSS116 DOT-3	

▼ Capacities

(Approximate Quantities)

Item			Capacity
Engine oil	2.3-liter engine	With oil filter replacement	4.3 L (4.5 US qt, 3.8 Imp qt)
		Without oil filter replacement	3.9 L (4.1 US qt, 3.4 Imp qt)
	3.0-liter engine	With oil filter replacement	5.7 L (6.0 US qt, 5.0 Imp qt)
		Without oil filter replacement	5.2 L (5.5 US qt, 4.6 Imp qt)
Coolant	2.3-liter engine		7.0 L (7.4 US qt, 6.2 Imp qt)
	3.0-liter engine		8.5 L (9.0 US qt, 7.5 Imp qt)
Manual transaxle oil	2.3-liter engine		2.87 L (3.03 US qt, 2.53 Imp qt)
	3.0-liter engine		2.3 L (2.4 US qt, 2.0 Imp qt)
Automatic transaxle fluid	2.3-liter engine		8.14 L (8.60 US qt, 7.16 Imp qt)
	3.0-liter engine		7.0 L (7.4 US qt, 6.1 Imp qt)
Fuel tank			68.0 L (18.0 US gal, 15.0 Imp gal)

Check oil and fluid levels with dipsticks or reservoir gauges.